

VMAX
STOCK CODE: 871332

PERFECT LIFTING FROM VMAX

1.0-3.5TON

BALANCE WEIGHT TYPE FORKLIFT



安徽维麦重工股份有限公司
ANHUI VMAX HEAVY INDUSTRY CO.,LTD

1.0-3.5TON DIESEL FORKLIFT TRUCK

MAIN INFORMATION

1	Manufacturer	Vmax										
2	Model	Unit	CPC20	CPCD20	CPC25	CPCD25	CPC30	CPCD30	CPC35	CPCD35		
3	Power type	Diesel										
4	Rated capacity	kg	2000		2500		3000		3500			
5	Load center	mm	500									
6	Operator type	Drive in seat										

SIZE

7	Max. lift height of mast with Load-backrest	mm	4030	4030	4250	4262
8	Max.lift height of fork(standard)	mm	3000	3000	3000	3000
9	Height of mast (standard)	mm	1995	1995	2085	2180
10	Free lift height(standard)	mm	170	170	160	170
11	Height of Load-backrest	mm	1010	1010	1240	1235
12	Distance from seat to overhead guard	mm	1005			
13	Overhead Guard Height	mm	2070	2070	2090	2090
14	Overall length without fork	mm	3480/2560		3800/2730	
15	Front overhang	mm	477	477	479	498
16	Rear overhang	mm	498	498	498.5	498.5
17	Wheel base	mm	1600	1600	1740	1740
18	The height of traction pin	mm	290	290	310	310
19	Min. ground clearance	mm	110	110	135	135
20	Overall width	mm	1170	1170	1225	1225
21	The distance between forks	mm	1024/200	1024/200	1060/250	1060/250
22	Tread(front /rear)	mm	970/970	970/970	1000/970	1000/970
23	Min. Turning radius(outside)	mm	2170	2240	2400	2420
24	Min. Turning radius(inside)	mm	160	160	200	200
25	Min. Intersecting aisle	mm	2200	2280	2380	2400
26	Mast tilt angle	deg	6° / 12°			
27	Fork size	mm	1070X100X40	1070X100X45	1070X125X45	1070X125X50

PERFORMANCE

28	Speeds	Max.Drive speeds(with/without full load)	km/h	18/20		18/20		18/20		18/20	
29		Lifting speeds (with /without full load)	mm/s	450/490		450/490		470/520		470/520	
30		Lowering speeds(with /without full load)	mm/s	520/490		520/490		550/520		550/520	
31	Max. tractive force(with/without full load)		KN	20/15	21/15	20/15.2	21/15.2	20/16	20/16	20/16.3	20/16.3
32	Max.grade ability (with/without full load)		%	21/20	27/20	18/20	23/20	20/20	20/20	15/20	16.5/20

WEIGHT

33	Total weight	kg	3400	3649	4380	4700
34	Weight Distribution full load (front/ rear)	kg	4788/532	5562/618	6543/727	7380/820
35	Weight Distribution zero load(front / rear)	kg	1328/1922	1420/2208	1708/2562	1880/2820

WHEELS AND TYRES

36	Quantity of wheels		2 X / 2			
37	Type of tyres		Penumatic tyres			
38	Tyres	Front	7.00-12-12PR	7.00-12-12PR	28X9-15-12PR	28X9-15-12PR
39		Rear	6.00-9-10PR	6.00-9-10PR	6.50-10-10PR	6.50-10-10PR
40	Driving Brake		Hydraumatic Pedal			
41	Parking Brake		Mechanical manual			

CONTROL DEVICE FOR DRIVING AND TRANSMITTING

42	Battery		V/AH	12 / 80		
43	Engine (standard)	Model		4D27G31	4D30G31	4D32G31
44		Rated output	kw/rpm	36.8/2650	36.8/2650	45/2605
45		Rated torque	N.m/rpm	156/1700~1900	174/1800~1900	198/1800
46		No.of cylinder		4-90X105	4-95X105	4-98X105
47		Displacement	L	2.67	2.98	3.168
48	Fuel tank capacity		L	60	60	70
49	Number of speeds for transmission		1-1 Hand shift transmission / 2-2 Power shift transmission			

1.0-3.5TON WIDE VIEW MAST

Mast type	Max.lift height (mm)	Rated capacity(load center:500mm)(kg)					Mast height(mm)				Mast tilt angle (front/rear)
		1.5TON	2TON	2.5TON	3TON	3.5TON	1.5TON	2-2.5TON	3TON	3.5TON	
M200	2000	1500	2000	2500	3000	3500	1490	1495	1565	1520	6/12
M250	2500	1500	2000	2500	3000	3500	1740	1745	1815	1770	6/12
M270	2700	1500	2000	2500	3000	3500	1840	1845	1915	1870	6/12
M300	3000	1500	2000	2500	3000	3500	1990	1995	2065	2120	6/12
M330	3300	1500	2000	2500	3000	3500	2140	2145	2215	2170	6/12
M350	3500	1500	2000	2500	3000	3500	2240	2245	2315	2270	6/12
M370	3700	1500	2000	2500	3000	3500	2340	2345	2415	2370	6/6 *6/6
M400	4000	1500	2000	2500	2850 *3000	3300 *3500	2540	2545	2615	2570	6/6 *6/6
M425	4250	1300 *1500	1850 *2000	2300 *2500	2850 *3000	3200 *3500	2665	2670	2740	2695	6/6 *6/6
M450	4500	1300 *1300	1600 *1900	2100 *2400	2600 *3000	2900 *3100	2790	2795	2865	2820	6/6 *6/6
M475	4750	950 *1300	1300 *1800	1800 *2100	2400 *2900	2550 *2850	2915	2920	2990	2945	6/6 *6/6
M500	5000	950 *1150	1200 *1700	1600 *1900	2100 *2850	2400 *2750	3040	3045	3115	3070	6/6 *6/6
M550	5500	*1000	950 *1500	1200 *1700	*2400	1800 *2400	3340	3345	3415	3370	*3/6
M600	6000	*650	800 *1200	900 *1400	*2000	1400 *2200	3590	3595	3665	3620	*3/6

Remarks: (1) *represents the load capacity fitted with double front tyres (2) The max.lift height with backrest:+580mm

1.0-3.5TON WIDE VIEW FULL FREE 2-STAGE MAST

Mast type	Max.lift height (mm)	Rated capacity(load center:500mm)(kg)					Mast height(mm)					Free lifting(with backrest)				Mast tilt angle (front/rear)
		1.5TON	2TON	2.5TON	3TON	3.5TON	1.5TON	2-2.5TON	3TON	3.5TON	4TON	1.5TON	2-2.5TON	3TON	3.5TON	
ZM200	2000	1500	2000	2500	3000	3500	1490	1495	1565	1680	1650	475	495	325	560	6/12
ZM250	2500	1500	2000	2500	3000	3500	1740	1745	1815	1930	1900	725	745	575	710	6/12
ZM270	2700	1500	2000	2500	3000		1840	1845	1915		2000	825		675		6/12
ZM300	3000	1500	2000	2500	3000	3500	1990	1995	2065	2180	2150	975	995	825	960	6/12
ZM330	3300	1500	2000	2500	3000	3500	2140	2145	2215	2330	2300	1125	1145	975	1100	6/12
ZM350	3500	1500	2000	2500	3000	3500	2240	2245	2315	2430	2400	1225	1245	1075	1210	6/12
ZM370	3700	1500	2000	2500	2850 *3000	3500	2340	2345	2415	2530	2500	1325	1370	1175	1335	6/12
ZM400	4000	1500	2000	2500	2700 *3000	3200 *3500	2540	2545	2615	2730	2700	1525	1545	1375	1510	6/12
ZM425	4250	1400 *1500	1900 *2000	2250 *2500	2550 *2850	3100 *3200	2665	2670	2740	2855	2825	1650	1670	1500	1635	6/6 *6/12
ZM450	4500	1300 *1400	1800 *1900	2150 *2400	2400 *2700	3000 *3050	2790	2795	2865	2980	2950	1775	1795	1625	1765	6/6 *6/6
ZM475	4750				2200 *2550	3000 *3050			2990		3075			1750		6/6 *6/6
ZM500	5000	1000 *1350	1600 *1700	1650 *2200	2000 *2400	2500 *2850	3040	3045	3115	3230	3200	2025	2045	1875	2010	6/6 *6/6
ZM550	5500	*1100	*1600	*1950	1600 *2200	*2500	3340	3345	3415	3530	3500	2325	2345	2175	2310	*3/6
ZM600	6000	*800	*1500	*1800	1200 *1900	*2300	3590	3595	3670	3780	3750	2575	2595	2450	2560	*3/6

Remarks: (1)The free lifting height (without backrest):1.5Ton: +514mm; 2-2.5Ton: +435mm; 3-3.5Ton: +580mm; 4Ton: +535mm
(2) * represents the load capacity fitted with double front tyres

1.0-3.5TON WIDE VIEW FULL FREE 3-STAGE MAST

Mast type	Max.lift height (mm)	Rated capacity(load center:500mm)(kg)				Mast height(mm)					Free lifting(with backrest)			Mast tilt angle (front/rear)
		2TON	2.5TON	3TON	3.5TON	2-2.5TON	3TON	3.5TON	4TON	4.5TON	2-2.5TON	3TON	3.5TON	
ZM360	3600	2000	2500	3000	3500	1695	1765	1820	1860	2080	655	528	588	6/6 *6/6
ZM400	4000	2000	2500	3000	3500	1830	1898	1953	1993	2213	788	661	721	6/6 *6/6
ZM420	4200	1850 *2000	2200 *2400	2850 *2900	3300 *3350	1895	1965	2020	2060	2280	855	728	788	6/6 *6/6
ZM435	4350	1750 *1900	1950 *2300	2800 *2850	3100 *3200	1945	2015	2070	2110	2330	905	778	838	6/6 *6/6
ZM450	4500	1750 *1800	2150 *2300	2700 *2800	2800 *2900	1995	2065	2120	2160	2380	995	828	888	6/6 *6/6
ZM480	4800	1700 *1800	1950 *2300	2500 *2800	2600 *2900	2095	2165	2220	2260	2480	1055	928	988	6/6 *6/6
ZM500	5000	1600 *1750	1650 *2250	2400 *2750	2450 *2850	2165	2232	2287	2327	2547	1121	995	1055	6/6 *6/6
ZM550	5500	1450 *1700	1500 *2150	2250 *2650	2300 *2700	2330	2398	2453	2493	2713	1288	1161	1221	3/6 *3/6
ZM600	6000	950 *1600	1000 *1800	1500 *2100	1550 *2200	2550	2615	2670	2710	2930	1505	1378	1438	3/6 *3/6

Remarks (1)The free lifting height (without backrest): 2-2.5Ton: +435mm; 3-3.5Ton: +580mm; 4.5Ton: +535mm
(2) * represents the load capacity fitted with double front tyres



	1	
2		4
3		5

1. Electro-hydraulic reversing handle

Adopt electro-hydraulic reversing handle to ensure easy operation, reducing the labor intensity effectively.

2. Instrument panel & meter display

Fix the instrument panel with concise meter on right side, ensure the driver read and understand easily.

3. New design overhead guard

Heightening overhead guard with big circular arc structure of front legs enlarge the operating space and expand visual field, reducing the driving fatigue.

4. New type wide view stable mast

Original imported German U-steel as optional together with advanced welding process and technology make the mast more stable and durable.

5. Security system

Equipped with OPS system as optional. When the operator leaves the seat during operation, the system will cut off the driving power to avoid accident happens.

1.0-3.5TON

BALANCE WEIGHT
TYPE FORKLIFT



安徽维麦重工股份有限公司
ANHUI VMAX HEAVY INDUSTRY CO.,LTD

Add: No.18 South Shengli Road, Jin'an Development Area, Lu'an, Anhui Province, China
Tel: +86-564-3835570 400-0564-222 Fax: +86-564-3835570
Email: info@vmaxchina.com Web: www.vmaxchina.net



wechat



website